Zoe Competition







Allows to effectively work in any light condition



To accurately and reliably time coffee extraction





EASY SERVICE

Fast access to the internal parts for quick and easy technical service

LOW SERVICE COST

Designed to decrease the maintenance and inspection costs

_Characteristics

of brewing.



ACTIVATED ELECTRONIC PRE-INFUSION

Management of the delayed activation of water solenoid in the first phase

DOUBLE READING GAUGE

Allows to control at the same time

the boiler pressure and the

distribution pressure.

EASY SERVICE Fast access to the internal

parts for quick and easy technical service.





AUTOMATIC CLEANING CYCLE Process for coffee



groups cleaning.



LED LIGHTING OF THE WORK AREA Allows efficient working in any condition of environmental lighting.



SHOT TIMER To accurately and reliably time coffee extraction.

_Optional



AUTOSTEAMER

Steam wand characterized by an electronic system that allows to mount and/or heat milk at the set temperature.



CUP WARMER Dedicated resistor to keep all the cups at the optimal temperature.











SANREMO




Versions



1 group	2 group
1 steam tap	2 steam taps
1 water tap	1 water tap
1 one-cup filter hoder	1 one-cup filter hoder
1 two-cup filter hoder	2 two-cup filter hoders







2-3 group

_Technical data		1 group	2 group	3 group
voltage	٧	220-2	40 1N / 380-4	15 3N
power imput	kW	2.35	3.15	5.8
steam boiler capacity	It	5	9	12.5
steam boiler power	kW	1.95	2.7	5.1
pump power	kW	0.15	0.15	0.15
net weight	lb / kg	93 / 42	121 / 55	152 / 69
gross weight (with shipping crate)	lb / kg	104 / 47	130 / 59	161 / 73





Colours

Black	RAL 9005
White Black	RAL 9003 9005
White Matte black	RAL 9003 9005
White Red	RAL 9003 3002

PERSONALISED GRAPHICS





